

REV.	DESCRIPTION	DATE
A	RELEASE	Nov 15, 2005
B	05'1232	Dec 16, 2005
C	05'1244	Dec 22, 2005
D	06'0121	Jan 16, 2006
E	06'0229	Feb 20, 2006
F	06'0514	May 08, 2006
G	06'121B	Dec 12, 2006
H	07'0501	May 05, 2007

ORDER INFORMATION :

5190008-XXX-R



SERIES CODE: L ROHS
 SMT: FOLLOW NUMBER
 FEMALE: 09: TUBE PACKAGE
 NUMBER OF POSITIONS: 10: TAPE&REEL PACKAGE
 CONTACT PLATING: 0: GOLD FLASH
 3: GOLD 15 μ

MATERIALS:

- HOUSING : HI-TEMP. PLASTIC (UL 94V-0),BLACK.
- TERMINAL : COPPER ALLOY(T=0.15mm).
GOLD PLATED OVER NICKEL.
- SHELL : STAINLESS STEEL(T=0.15mm).
NICKEL PLATED OVERALL.

SPECIFICATION

- CURRENT RATING : 0.5 A MAX.
- DIELECTRIC WITHSTANDING VOLTAGE :
500V AC R.M.S. FOR ONE MINUTE.
- CONTACT RESISTANCE :30m Ω MAX.
- INSULATION RESISTANCE : 1000 M Ω MIN. AT 500V DC.
- OPERATING TEMPERATURE : -25°C TO +85°C.






RECOMMEND PAD LAYOUT
 TOLERANCE: ±0.05
 TOP VIEW



PIN NO.	NAME	TYPE	DESCRIPTION
1	DAT2	I/O/PP	Data Line[bit2]
2	CD/DAT3 ²	I/O/PP ³	Card Detect/Data Line[bit3]
3	CMD	PP	Command/Response
4	V _{DD}	S	Supply Voltage
5	CLK	I	Clock
6	V _{SS}	S	Supply Voltage Ground
7	DAT0	I/O/PP	Data Line[bit0]
8	DAT1	I/O/PP	Data Line[bit1]

TOLERANCE .0=±0.25[.010] .00=±0.15[.006] .000=±0.05[.002] ANG.=±3°		DRAWER <i>gun</i>		Astron ASTRON TECHNOLOGY CORP. NAME T-FLASH CARD CONN
CHECK <i>Eric</i>		APP'D <i>Dunkern</i>		
UNITS : mm [inch]		PRODUCT SPEC. ---		
SCALE NONE	SIZE A4	SHEET 1 OF 3	REV. H	DRAW NO. R5190008-X09(10)-R






REV.	DESCRIPTION	DATE
A	RELEASE	Nov 15, 2005
B	05'1232	Dec 16, 2005
C	05'1244	Dec 22, 2005
D	06'D121	Jan 16, 2006
E	06'D229	Feb 20, 2006
F	06'D514	May 08, 2006
G	06'1218	Dec 12, 2006
H	07'0501	May 05, 2007



T-FLASH CARD DIMENSION

TOLERANCE .0=±0.20 .00=±0.10 .000=±0.05 ANG.=±3°		DRAWER <i>yun</i>	 ASTRON TECHNOLOGY CORP.
		CHECK <i>Eric</i>	
UNITS : mm [inch]		APP'D <i>Dunken</i>	DRAW NO. R5190008-X09(10)-R
SCALE NONE	SIZE A4	SHEET 2 OF 3	REV. H

REV.	DESCRIPTION	DATE
A	RELEASE	Nov 15, 2005
B	05'1232	Dec 16, 2005
C	05'1244	Dec 22, 2005
D	06'0121	Jan 16, 2006
E	06'0229	Feb 20, 2006
F	06'0514	May 08, 2006
G	06'1218	Dec 12, 2006
H	07'0501	May 05, 2007



TAPE & REEL PACKAGE :

MATERIALS

1. CARRIER TAPE: POLYSTYREN (PS)
2. COVER TAPE: POLYSTYREN (PS)
3. REEL: POLYSTYREN (PS)

QUANTITY

1. 1200 PCS PER REEL
2. 10 REEL PER CARTON(12000 PCS PER CARTON)

TOLERANCE .0=±0.30 .00=±0.10 .000=±0.05 ANG.=±3°	DRAWER <i>yun</i>		 ASTRON TECHNOLOGY CORP.
	CHECK <i>Eric</i>		
APP'D <i>Dunkan</i>		NAME	
PRODUCT SPEC.		T-FLASH CARD CONN	
UNITS : mm			DRAW NO.
SCALE NONE	SIZE A4	SHEET 3 OF 3	REV. H
			R5190008-X09(10)-R